



Aerodynamic Optimization of Electric Vehicles and Its Influence on Energy Efficiency and Vehicle Performance

Adrian Keller*

Department of Automotive Engineering, Technical University of Munich, Munich, Germany

DESCRIPTION

Aerodynamic optimization of electric vehicles focuses on reducing the resistance encountered by a vehicle as it moves through air, thereby improving energy efficiency, extending driving range and enhancing overall performance stability. In electric mobility systems, aerodynamic behavior plays a significantly larger role compared to traditional combustion vehicles because energy storage in batteries is limited and every reduction in energy consumption directly translates into increased operational distance. The external shape of an electric vehicle determines how air flows around it and even minor modifications in surface geometry can produce measurable differences in drag forces. Engineers analyze airflow behavior using computational fluid dynamics simulations and wind tunnel experiments to refine vehicle profiles, underbody structures, wheel designs and surface transitions. The objective is to minimize turbulence generation and maintain smooth airflow attachment over the vehicle body for as long as possible before separation occurs.

A major aspect of aerodynamic development involves reducing the coefficient of drag, which quantifies resistance caused by air movement relative to the vehicle. Electric vehicles benefit from elongated rooflines, smooth underbodies and enclosed wheel designs that limit airflow disruption. The absence of large engine cooling requirements, compared to internal combustion vehicles, allows designers more flexibility in shaping front-end geometry. This enables the creation of more streamlined profiles that reduce pressure differences between the front and rear sections of the vehicle. However, designers must still consider cooling needs for battery packs, power electronics and motor assemblies, which require controlled airflow pathways without significantly increasing drag levels.

Underbody airflow management is another critical area of aerodynamic refinement. Traditional vehicles often have uneven undercarriages due to exhaust systems, transmission components and fuel tanks, which increase turbulence. Electric vehicles, by

contrast, typically feature flatter underbodies, allowing air to pass more smoothly beneath the chassis. Additional components such as aerodynamic shields and diffusers are used to guide airflow toward the rear of the vehicle in a controlled manner, reducing wake formation and pressure drag. The interaction between the underbody airflow and rear diffuser geometry has a strong influence on vehicle stability at higher speeds.

Wheel and tire design also contributes significantly to aerodynamic performance. Rotating wheels generate localized turbulence that increases drag. To address this, engineers often design wheel covers or specialized spoke structures that reduce air disturbance. Tire sidewall shapes and tread patterns are also evaluated for their interaction with airflow. In some cases, partial wheel fairings are introduced to guide air around rotating surfaces more efficiently. These modifications must balance aerodynamic benefits with cooling requirements for braking systems and mechanical durability under various driving conditions.

Rear-end design is another important factor in aerodynamic efficiency. The wake region behind a vehicle is a major source of drag due to low-pressure zones that form as air separates from the body. Electric vehicles often incorporate tapered rear sections, integrated spoilers and subtle diffuser elements to reduce wake size and stabilize airflow detachment. Hatchback and sedan configurations are optimized differently, with sedans typically achieving lower drag coefficients due to smoother rear tapering. The design of rear lights, bumpers and trunk edges is also adjusted to minimize airflow disruption while maintaining functional and aesthetic requirements.

CONCLUSION

The evolution of aerodynamic optimization in electric vehicles continues to progress alongside advancements in materials, computational methods and manufacturing techniques. Lightweight composite materials allow more flexible shaping of vehicle surfaces, while additive manufacturing enables complex

Correspondence to: Adrian Keller, Department of Automotive Engineering, Technical University of Munich, Munich, Germany, E-mail: samuel.whitaker@manchester.ac.uk

Received: 27-Jan-2026, Manuscript No. JAME-26- 31562; **Editor assigned:** 29-Jan-2026, PreQC No. JAME-26- 31562 (PQ); **Reviewed:** 12-Feb-2026, QC No. JAME-26-31562; **Revised:** 19-Feb-2026, Manuscript No. JAME-26-31562 (R); **Published:** 26-Feb-2026, DOI: 10.35248/2252-5211.26.15.539.

Citation: Keller A (2026). Aerodynamic Optimization of Electric Vehicles and Its Influence on Energy Efficiency and Vehicle Performance. J Appl Mech Eng. 15:539.

Copyright: © 2026 Keller A. This is an open-access article distributed under the terms of the Creative Commons Attribution License, which permits unrestricted use, distribution and reproduction in any medium, provided the original author and source are credited.

geometric structures that were previously difficult to produce. These developments contribute to more refined control over airflow behavior and vehicle efficiency. As electric mobility expands across global markets, aerodynamic engineering remains a significant area of focus for improving operational efficiency, stability and overall vehicle performance characteristics within

diverse driving environments. Energy consumption in electric vehicles is directly influenced by aerodynamic efficiency, especially at higher speeds where air resistance increases exponentially. Even small reductions in drag can produce noticeable improvements in driving range.