



Enzyme Immobilization: Improving Biocatalyst Stability and Reusability for Industrial Applications

Hiroshi Tanaka *

Department of Biochemical Engineering, Kyoto International University, Kyoto, Japan

DESCRIPTION

Enzyme immobilization is a biotechnology approach in which enzymes are confined, attached, or enclosed within a suitable insoluble material while retaining their catalytic activity. Free enzymes can perform biochemical reactions efficiently, but their separation from reaction mixtures may be difficult, particularly when they are present in small quantities. Immobilization provides a practical method for recovering enzymes after a reaction and using them repeatedly. This characteristic has increased the value of immobilized enzymes in food processing, pharmaceutical manufacturing, environmental treatment, biofuel production and chemical synthesis. Enzymes are biological catalysts that accelerate specific chemical reactions under relatively mild conditions. Their activity depends strongly on temperature, pH, solvent composition, substrate concentration and the presence of inhibitors. When an enzyme is immobilized, its interaction with the surrounding material can alter its physical and catalytic properties. A suitable immobilization method can improve resistance to unfavorable conditions while maintaining sufficient access to the active site. The selection of the immobilization technique and support material is therefore important for obtaining efficient catalytic performance.

Several approaches are available for immobilizing enzymes. Adsorption is one of the simplest methods and involves attaching an enzyme to the surface of a solid support through weak interactions such as hydrogen bonding, ionic interactions, hydrophobic forces, or van der Waals interactions. Materials used for adsorption include silica, activated carbon, polymers and certain mineral surfaces. The method generally requires relatively simple processing and can preserve enzyme structure because strong chemical modification may not be necessary. However, weak attachment can sometimes result in enzyme release during prolonged operation. Covalent attachment provides stronger association between an enzyme and its

support. In this approach, functional groups on the enzyme interact chemically with reactive groups present on the supporting material. Amino, carboxyl, sulfhydryl and hydroxyl groups can participate in different coupling reactions. Covalent immobilization can reduce enzyme loss during repeated processing and may provide good operational stability. Excessive chemical modification, however, can reduce catalytic activity if important structural regions near the active site are affected.

Entrapment is another widely used technique. In this method, enzymes are enclosed within a porous matrix that allows substrates and products to move through the material. Calcium alginate, polyacrylamide, silica-based matrices and other polymers can be used for this purpose. Entrapment can protect enzymes from direct exposure to certain environmental conditions while allowing catalytic reactions to occur inside the matrix. The size and distribution of pores are important because large substrates may diffuse slowly through dense materials. Encapsulation involves enclosing enzymes within a membrane or semipermeable structure. The membrane allows selected molecules to pass while retaining the enzyme inside the compartment. This arrangement can provide physical protection and facilitate enzyme recovery. Encapsulated enzymes are useful when the catalyst needs to remain separated from the bulk reaction mixture while substrates and products can still move between the internal and external environments.

Cross-linking represents another method in which enzyme molecules are connected to one another through chemical bridges. Cross-linked enzyme aggregates can be prepared without requiring a conventional solid support. This approach can produce catalyst particles containing a high proportion of enzyme. Such preparations can display improved resistance to washing and may be suitable for repeated use. The cross-linking conditions must be controlled carefully because excessive chemical modification can affect enzyme conformation and activity. The choice of support material strongly influences

Correspondence to: Hiroshi Tanaka, Department of Biochemical Engineering, Kyoto International University, Kyoto, Japan, E-mail: hiroshi.tanaka@kiu.jp

Received: 29-Aug-2025, Manuscript No. JMBT-25-32549; **Editor assigned:** 01-Sept-2025, PreQC No. JMBT-25-32549 (PQ); **Reviewed:** 15-Sept-2025, QC No. JMBT-25-32549; **Revised:** 22-Sept-2025, Manuscript No. JMBT-25-32549 (R); **Published:** 29-Sept-2025, DOI: 10.35248/1948-5948.25.17.656

Citation: Tanaka H (2025). Enzyme Immobilization: Improving Biocatalyst Stability and Reusability for Industrial Applications. J Microb Biochem Technol. 17:656.

Copyright: © 2025 Tanaka H. This is an open-access article distributed under the terms of the Creative Commons Attribution License, which permits unrestricted use, distribution and reproduction in any medium, provided the original author and source are credited.

immobilized enzyme performance. An ideal support should provide suitable surface characteristics, chemical compatibility, mechanical stability and sufficient accessibility for substrates. Silica, cellulose, agarose, chitosan, synthetic polymers, magnetic particles and porous ceramics are among the materials used in enzyme immobilization. Natural polymers can offer useful biological compatibility, while synthetic materials can provide adjustable chemical and physical properties.

Mass transfer is an important consideration in immobilized enzyme systems. In a free enzyme solution, substrates can directly interact with enzyme molecules. After immobilization, substrates must move through the surrounding medium and sometimes through pores within the support before reaching catalytic sites. Products must then travel away from these sites. If

diffusion is slow, the observed reaction rate may decrease even when the immobilized enzyme itself retains substantial catalytic activity. Particle size, pore structure, enzyme loading, agitation and substrate properties can influence this process. Immobilization can also affect enzyme stability. Enzymes may lose their active structure when exposed to elevated temperatures, unsuitable pH conditions, organic solvents, or mechanical stress. Attachment to an appropriate support can restrict excessive molecular movement and provide a more favorable microenvironment. As a result, certain immobilized enzymes can maintain activity for longer periods than their free counterparts. The extent of this improvement varies according to the enzyme, support, attachment method and reaction conditions.