OPEN ACCESS Freely available online

ISSN: 2157-7110
Journal of Food Processing & Technology

Commentary

Food Rheology: Understanding Flow and Deformation in Food Processing

Caelan Whitmore*

Department of Food Rheology and Process Engineering, University of Edinburgh, Edinburgh, United Kingdom

DESCRIPTION

Food rheology is the study of how food materials deform and flow when subjected to external forces. It provides a scientific basis for understanding the physical behavior of foods during processing, handling, storage, transportation, and consumption. Foods rarely behave as simple liquids or solids because they contain complex combinations of water, proteins, carbohydrates, fats, fibers, minerals, and other components. Their physical response can change with temperature, moisture content, shear rate, pressure, composition, and processing history. Understanding these changes enables food processors to design equipment, control product consistency, optimize formulations, and develop foods with desirable textural and sensory characteristics.

The rheological behavior of a food is commonly described through properties such as viscosity, elasticity, yield stress, and viscoelasticity. Viscosity represents the resistance of a fluid to flow, while yield stress refers to the minimum applied stress required for some materials to begin flowing. Elastic behavior describes the ability of a material to recover part of its deformation after an applied force is removed. Many foods exhibit both viscous and elastic characteristics and are therefore described as viscoelastic materials. Dough, yogurt, sauces, chocolate, cheese, fruit purees, and gels are examples of food systems whose processing behavior depends strongly on their rheological properties.

Food materials can display different flow patterns depending on the relationship between applied stress and deformation rate. Newtonian fluids exhibit relatively constant viscosity under a given temperature and pressure, whereas non-Newtonian fluids show viscosity changes with shear rate. Many food products are shear-thinning, meaning their apparent viscosity decreases as the shear rate increases. Ketchup, yogurt, salad dressings, and some fruit concentrates commonly demonstrate this type of behavior. Shear-thinning characteristics can be desirable because a product may remain stable at rest while becoming easier to pour or spread during use. Other foods may exhibit shear-thickening behavior, in which apparent viscosity increases with increasing shear rate under suitable conditions.

Temperature has a strong influence on food rheology. Increasing temperature generally decreases the viscosity of many liquid and semi-liquid foods because molecular movement becomes greater and intermolecular interactions may weaken. However, heating can also initiate structural transformations that produce different rheological responses. Starch gelatinization, protein denaturation, melting of fats, and formation of gels can substantially change the flow properties of a food. During cooling, some systems may develop a stronger structure because of starch retrogradation, protein interactions, crystallization, or gel formation. Monitoring rheological changes during heating and cooling can therefore provide useful information for designing thermal processing conditions.

Moisture content is another major factor affecting rheological behavior. Water acts as a plasticizing agent in many food systems and can reduce resistance to deformation. In dough and bakery products, changes in water availability influence mixing behavior, elasticity, extensibility, and final texture. In powders and particulate foods, moisture can promote particle adhesion and affect flowability. Controlling moisture is consequently important not only for product quality but also for equipment performance and storage stability.

Rheological measurements are widely used in product formulation and quality control. Instruments such as rotational rheometers, viscometers, texture analyzers, and dynamic mechanical analyzers can measure different aspects of food behavior. Rotational measurements can determine apparent viscosity at different shear rates, while oscillatory tests can provide information about elastic and viscous components. Texture measurements can complement rheological data by assessing firmness, cohesiveness, adhesiveness, and related characteristics. The selection of an appropriate test depends on the food structure and the processing or sensory property being investigated.

In industrial food processing, rheology influences pumping, mixing, filling, coating, extrusion, spraying, and heat transfer. A

Correspondence to: Caelan Whitmore, Department of Food Rheology and Process Engineering, University of Edinburgh, Edinburgh, United Kingdom, E-mail: caelan.whitmore@ed.ac.uk

Received: 15-Sep-2025, Manuscript No. JFPT-25-32832; **Editor assigned:** 17-Sep-2025, Pre QC No. JFPT-25-32832; **Reviewed:** 01-Oct-2025, QC No. JFPT-25-32832; **Revised:** 08-Oct-2025, Manuscript No. JFPT-25-32832; **Published:** 15-Oct-2025, DOI: 10.35248/2157-7110.25.16.1181

Citation: Whitmore C (2025). Sustainable Food Rheology: Understanding Flow and Deformation in Food Processing. J Food Process Technol. 16:1181.

Copyright: ©2025 Whitmore C. This is an open-access article distributed under the terms of the Creative Commons Attribution License, which permits unrestricted use, distribution, and reproduction in any medium, provided the original author and source are credited.

highly viscous product requires greater pumping energy and may need specialized equipment. Changes in viscosity can also affect flow through pipes and heat exchangers, influencing processing time and temperature distribution. During mixing, rheological properties determine the energy required to achieve uniform dispersion of ingredients. In extrusion processing, the relationship between shear, temperature, and viscosity affects material movement through the extruder and the characteristics of the final product.

Rheology also contributes to the development of plant-based and alternative food products. Formulations containing plant proteins, starches, fibers, oils, and hydrocolloids can produce complex flow and deformation behavior. Rheological measurements can help researchers understand how processing conditions influence protein networks, emulsions, gels, and other structures. This information can assist in adjusting formulations to obtain appropriate viscosity, stability, mouthfeel, and processing performance. Hydrocolloids such as pectin, xanthan gum, carrageenan, and guar gum are frequently used to modify rheological properties, although their effects depend on concentration, pH, ionic conditions, temperature, and interactions with other ingredients.

Food rheology is also closely related to sensory perception. Consumers experience viscosity, creaminess, thickness, spreadability, firmness, and other textural characteristics during eating. Instrumental rheological measurements cannot completely reproduce human perception, but they provide useful physical information that can be related to sensory observations. Combining rheological measurements with sensory analysis can help food manufacturers establish product specifications and improve consistency between production batches.

In conclusion, food rheology provides an important scientific framework for understanding the flow, deformation, and structural behavior of food materials. Its applications extend from ingredient selection and formulation to processing equipment design, quality control, storage, and sensory evaluation. Knowledge of viscosity, viscoelasticity, yield stress, and temperature-dependent behavior allows food processors to improve manufacturing efficiency and maintain consistent product characteristics. Continued development of advanced rheological instruments, mathematical models, and digital processing systems will expand the ability to predict food behavior and design products with specific physical and sensory properties.