



Root-Zone Sensor Fusion for Accurate Soil Moisture and Crop Water Management

Jichao Tang*

Department of Agricultural Technology, Southeast Asia University of Agricultural Sciences, Kuala Lumpur, Malaysia

DESCRIPTION

Root-zone sensor fusion is an approach in agricultural technology that combines measurements from multiple sensors to provide a more complete understanding of conditions around plant roots. The root zone is the portion of soil where most active roots obtain water, oxygen, and nutrients. Conditions within this zone can vary significantly with depth, soil texture, temperature, irrigation, rainfall, and crop development. Accurate monitoring of these variations helps farmers determine when crops require water and how much irrigation should be applied. Sensor fusion improves decision-making by integrating data from multiple sensing devices rather than relying on a single measurement source.

Soil moisture is one of the most important variables monitored within the root zone. Plants require adequate water for photosynthesis, nutrient transport, cell development, and other physiological processes. Water deficiency can reduce plant growth and yield, while excessive moisture can limit oxygen availability in the root zone and increase nutrient leaching. A single soil moisture sensor provides information for a specific point and depth, but it may not represent conditions across the entire root zone. Using multiple sensors at different depths and locations provides a more complete representation of soil water distribution.

Root-zone sensor fusion integrates data from sensors that measure volumetric water content, soil temperature, electrical conductivity, matric potential, and related soil properties. These measurements are collected at regular intervals and transmitted to a central data system. The system compares readings from different sensors to identify spatial and temporal changes in soil conditions. When combined with crop data and weather information, these measurements support more accurate irrigation decisions.

Sensor placement is a critical factor in root-zone monitoring. Sensors placed near the soil surface respond quickly to rainfall and evaporation but may not reflect water availability in deeper

root layers. Sensors installed deeper in the soil provide information about water storage below the active root zone. Using multiple depths allows observation of water movement after irrigation or rainfall and plant water uptake across soil layers. Placement decisions should consider crop type, root depth, soil structure, irrigation method, and field conditions.

Different crops have different root architectures, which affects optimal sensor depth selection. Shallow-rooted crops depend more on moisture in upper soil layers, while deep-rooted crops access water from deeper zones. Perennial crops such as fruit trees often require monitoring across multiple depths due to extensive root systems. A sensor fusion system can integrate measurements from different depths and interpret them according to crop-specific rooting characteristics.

Soil texture strongly influences water movement and retention. Sandy soils allow rapid drainage, while clay soils retain water for longer periods. Loam soils exhibit intermediate behavior. Multi-depth sensor networks help identify how water moves through different soil types and whether irrigation water remains within the active root zone or percolates beyond it.

Weather data provides an additional layer of information for interpreting soil moisture dynamics. Rainfall, air temperature, humidity, solar radiation, and wind speed all influence evapotranspiration and crop water demand. By combining weather data with soil measurements, sensor fusion systems can estimate changes in water availability more accurately. For example, high temperatures and strong winds increase water loss, while rainfall reduces irrigation requirements. This integration supports irrigation decisions based on real-time field conditions rather than fixed schedules.

Sensor fusion also improves data reliability by identifying inconsistent or faulty measurements. Soil sensors may produce errors due to poor soil contact, calibration drift, damage, or communication failures. When multiple sensors are used, the system can compare readings and detect outliers that deviate

Correspondence to: Jichao Tang, Department of Agricultural Technology, Southeast Asia University of Agricultural Sciences, Kuala Lumpur, Malaysia, E-mail: jichao.tang@seaus.edu.m

Received: 01-Dec-2025, Manuscript No. AGT-25-32503; **Editor assigned:** 03-Dec-2025, Pre QC No. AGT-25-32503 (PQ); **Reviewed:** 17-Dec-2025, QC No. AGT-25-32503; **Revised:** 23-Dec-2025, Manuscript No. AGT-25-32503 (R); **Published:** 31-Dec-2025, DOI:10.35248/2168-9891.25.14.429

Citation: Tang J (2025) Root-Zone Sensor Fusion for Accurate Soil Moisture and Crop Water Management. Agrotechnology. 14:429.

Copyright: © 2025 Tang J. This is an open access article distributed under the terms of the Creative Commons Attribution License, which permits unrestricted use, distribution, and reproduction in any medium, provided the original author and source are credited.

significantly from surrounding measurements. This helps reduce the influence of inaccurate data on irrigation decisions.

CONCLUSION

Root-zone sensor fusion provides a practical framework for improving irrigation management and understanding soil water dynamics. By combining multiple sensor measurements with

weather, crop, and irrigation data, it enables more precise water management decisions. This approach supports improved irrigation efficiency, reduced water loss, better nutrient management, and more stable crop production. Continued advancements in sensor technology, data analytics, and automation are expected to further enhance its role in modern agriculture.