OPEN ACCESS Freely available online

ISSN: 2155-9546
Journal of Aquaculture Research & Development

Perspective

Underwater Computer Vision for Intelligent Monitoring in Aquaculture Systems

Kristin Brox*

Department of Aquatic Systems, Norwegian University of Science and Technology (NTNU), Trondheim, Norway

DESCRIPTION

Underwater computer vision is becoming an important digital method for observing fish, shrimp, and other aquatic organisms in aquaculture facilities. Conventional farm monitoring often depends on direct observation, manual sampling, periodic weighing, and visual inspection by farm personnel. These approaches can provide useful information, but they require considerable time and may not capture changes continuously. Underwater cameras combined with image processing and machine learning can provide repeated observations without removing animals from their culture environment. This approach allows producers and researchers to collect visual information about animal behavior, body size, swimming activity, feeding responses, population distribution, and physical abnormalities.

An underwater computer vision system generally consists of cameras, illumination equipment, image acquisition hardware, data storage, and software for image analysis. Cameras can be positioned inside tanks, ponds, raceways, cages, or recirculating aquaculture systems. The equipment records images or video while aquatic animals move through the monitored area. Software then processes these visual data to identify individual animals or groups and measure selected characteristics. Depending on the application, the system may estimate body length, detect movement, classify behavior, count animals, identify feeding activity, or recognize unusual swimming patterns.

Water creates several technical difficulties for visual monitoring. Light is absorbed and scattered as it travels through water, while suspended particles can reduce image clarity. Algae, bubbles, organic material, and surface reflections may also interfere with image interpretation. Fish can overlap with one another, move rapidly, or change direction unexpectedly. These conditions make underwater image analysis different from ordinary computer vision applications performed in controlled terrestrial environments. Camera selection, installation depth, viewing angle, illumination, image resolution, and water quality therefore have a direct effect on the quality of collected data.

Image preprocessing is commonly applied before automated analysis. Noise reduction can remove unwanted visual disturbances, while contrast adjustment can improve separation between animals and the surrounding water. Image stabilization can reduce the effect of camera movement caused by water currents or equipment vibration. Background subtraction can assist in separating moving animals from stationary structures. More advanced systems use deep learning models to recognize animals even when the background is variable. These processing methods can reduce the amount of manual review required when large quantities of video are collected.

Fish counting is one of the practical applications of underwater computer vision. Counting animals manually can become difficult when stock density is high. A camera system can continuously record a defined section of a culture unit and use object detection algorithms to estimate the number of animals passing through the viewing region. Tracking algorithms can follow movement across consecutive frames and reduce the possibility of counting the same fish multiple times. Such information can support stock estimation, production planning, biomass assessment, and routine farm management.

Body-size estimation is another useful application. Fish length and body shape can be estimated from images when the camera position and scale are properly calibrated. Some systems use reference objects or known distances within the camera view to convert pixel measurements into physical dimensions. Repeated measurements can provide information about growth patterns without requiring frequent capture and handling. Reduced handling may also decrease stress associated with physical sampling. For commercial operations, continuous visual growth information could assist with feeding decisions, harvest planning, and production assessment. These technologies support efficient, non-invasive monitoring and improve overall aquaculture management.

Correspondence to: Kristin Brox, Department of Aquatic Systems, Technical University of Denmark (DTU), Lyngby, Denmark, E-mail: kristin.brox@ntnu.no

Received: 27-May-2026, Manuscript No. JARD-26-32739; **Editor assigned:** 29-May-2026, PreQC No. JARD-26-32739 (PQ); **Reviewed:** 12-Jun-2026, QC No. JARD-26-32739; **Revised:** 19-Jun-2026, Manuscript No. JARD-26-32739 (R); **Published:** 26-Jun-2026, DOI: 10.35248/2155-9546.26.17.1121

Citation: Brox K (2026). Underwater Computer Vision for Intelligent Monitoring in Aquaculture Systems. J Aquac Res Dev. 17:1121.

Copyright: © 2026 Brox K. This is an open access article distributed under the terms of the Creative Commons Attribution License, which permits unrestricted use, distribution, and reproduction in any medium, provided the original author and source are credited.

CONCLUSION

Underwater computer vision therefore represents a useful technological approach for collecting continuous visual information in aquaculture. Its applications extend from fish counting and size estimation to feeding assessment, behavioral analysis, health screening, welfare research, and environmental response monitoring. Successful implementation depends on appropriate camera placement, suitable lighting, reliable image processing, representative training data, and careful validation. When combined with environmental sensors and farm records, visual information can provide a broader understanding of aquatic animal performance and support more informed management decisions.